



HT-12000-SBL Series

HT-12000-SBL-M Monochrome HT-12000-SBL-C Color

Back-illuminated pixel structure





GEN**<i>**CAM





Back-illuminated 12.4 MP 10GigE camera with Sony Pregius S IMX545 CMOS sensor

HT-12000-SBL features the Sony Pregius S IMX545 sensor. The Sony Pregius S technology features back-illuminated pixel structure that delivers distortion-free, high imaging performance and miniaturization. At full resolution (4096 x 3000) you get up to 68 frames per second. With its 10GBaseT interface, sleek smaller case and CAT6A connection, this camera has the familiarity of GigE but with 10x the speed. Using CAT6A cabling, you can get cable lengths from 1 meter up to 100 meters. The HT-12000-SBL offers multi-camera synchronization at <1µs, low CPU overhead, and excellent priceperformance ratio.

Benefits

- » High-speed RJ45 10GBaseT interface
- » 10x the speed of GigE
- » GigE Vision[®] and Genicam[™] compliant
- » Back-illuminated pixel structure

Applications

- » Industrial inspection
- » Automation
- » Intelligent Transportation Systems
- » Logistics
- » Virtual reality
- » Volumetric capture
- » Referee Assist

Specifications

| Sensor | Sony IMX545 |
|-----------------------|--|
| Resolution | 4096 x 3000 |
| Megapixels | 12.4 MP |
| Sensor Type | 1/1.1 CMOS |
| Max Frame Rate | 68 fps @ 8-bit 46 fps @ 12-bit |
| Cell Size | 2.74μm x 2.74μm |
| Standard Mount | C Mount |
| Shutter | Global |
| Bit Depth | 8 & 12 bit |
| GPIO / Triggering | 3 in, 3 out Software, External (Pulse or Edge) |
| Interface | RJ45 10GBaseT |
| Exposure/Integration* | 5µs-1s |
| Dynamic Range | 74 dB |
| Monochrome Modes | Mono8, Mono12, Mono12Packed |
| Color Modes | RGB8, BGR8, YUV411, YUV422, YUV444 |
| Raw Modes | BayerRG8, BayerRG12, BayerRG12Packed |
| Operating System | Win10 (64 bit), Linux (64 bit) |
| Compliance | CE, FCC, RoHS, WEEE, GigE Vision, GenICam |
| Power Requirements | 9W, 12V |
| Operating Temperature | 0C- 45C |
| Storage Temperature | -30C to +60C |
| Dimensions & Weight | |
| Differisions & Weight | 88 x 58 x 39- 275g |

*all minimum exposure specs can vary from what is listed based on the limitations of each sensor as per notice from the manufacturer.



Mechanical drawings









